

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **11018378 A**

(43) Date of publication of application: **22 . 01 . 99**

(51) Int. Cl.

**H02K 15/06**

**H02K 1/16**

**H02K 3/48**

(21) Application number: **09162275**

(22) Date of filing: **19 . 06 . 97**

(71) Applicant: **DENSO CORP**


(72) Inventor:  
**NAKA YOSHIO**  
**NAKAMURA TADATSUGU**  
**MAEDA KAZUTAKA**  
**SUZUKI KAZUYOSHI**

(54) **STATOR OF ROTATING MACHINE AND  
MANUFACTURE THEREOF**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To facilitate a winding work, by winding a wire into a prescribed shape coil, connecting the coil wires in an aligned condition to each other, fixing the whole coil into a block, and mounting it on a stator core.

**SOLUTION:** A straight core 2A of a stator is constituted by laminating a plurality of core sheets 20. Pole teeth 2b for winding a coil 3 between respective adjacent slots 2a by forming a plurality of slots 2a in a longitudinal direction at equal pitches. In the coil 3, a coil wire 3a is wound previously in a circular shape to be formed into a prescribed shape coil. The coil wires 3a are connected to each other, and the whole coil 3 is fixed into a block, and is then inserted in the slot 2a across the periphery of one pole tooth 2b of the straight core 2A or two or more poles 2b. As a result, the coil shape is prevented from being broken at the time of assembly, insertion into the slot 2a is easy, and thus it is possible to conduct the winding work to a stator core easily.




COPYRIGHT: (C)1999,JPO







【圖1】




[圖3]




【例8】




【図4】




【图7】




【図 9】



**{ 0 1 0 }**



(四)



フロントページの続き

(72)發明者 鈴木 和義

愛知県刈谷市昭和町1丁目1番地 株式会社デンソー内